

# Blocking

4 COLOURS | 3 FINISHES | 7 SIZES



S  
O  
L  
U  
S

Floor:  
2PAD104

# Blocking

A concrete effect range that takes inspiration from natural elements such as rock, clay and limestone. Each tile features a smattering of gravel like speckles, creating a pleasant aesthetic quality.



Floor:  
2PAD103



Milldam  
2PAD101



Ballylig  
2PAD104



Tully  
2PAD102



Clinty  
2PAD103



Wall:  
2PAD101

	300x600 9mm	600x600 9mm	600x1200 9mm	750x750 9mm	750x1500 9mm	900x900 20mm	1200x1200 9mm
● Milldam	● \	● \	● \	● \	● \		● \
● Ballylig	● \	● \	● \	● \	● \		● \
● Tully	● \	● \	● \	● \	● \	△	● \
● Clinty	● \	● \	● \	● \	● \		● \

● Matt R10 (A+B)    \ Satin    △ Anti Slip R11 (A+B+C)

# Blocking

## APPEARANCE

Concrete

## MATERIAL

Porcelain

## USAGE

Floors and Walls

## SHADE VARIATION

V3 - Moderate

## SPECIAL PIECES


Available in all colours.

For more information contact our sales team.

## BATTISCOPIA

70x750mm

70x600mm



## ISO 10545 RESULTS

### 2. DIMENSIONS AND SURFACE QUALITY

Conforms

### 3. WATER ABSORPTION

0.2%

### 4. FLEXURAL STRENGTH

Conforms

### 6. DEEP ABRASION RESISTANCE

Conforms

### 8. LINEAR THERMAL EXPANSION

7 MK<sup>-1</sup>

### 9. THERMAL SHOCK RESISTANCE

Conforms

### 10. MOISTURE EXPANSION

No rating

### 12. FROST RESISTANCE

Conforms

### 13. CHEMICAL RESISTANCE

Conforms

### 14. STAIN RESISTANCE

Class 5

### SLIP RESISTANCE (DIN 51130)

Matt R10 (A+B)

Anti Slip R11 (A+B+C)

## MANUFACTURER CERTIFICATIONS:

### Declare.

EPD: Available

ISO 14001

ISO 17889-1

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to BS EN 16165:2021. HSE surface roughness and NCS Colour values are also available upon request. All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2024. 006.