

# Classico

4 COLOURS | 3 FINISHES | 5 SIZES | 4 SHAPES



S  
O  
L  
U  
S

Floor:  
3FEA104

# Classico

A modern interpretation of natural marble, Classico features expressive veining, multi tonal layers and is available in a palette of four neutral colours. In addition to standard sizes, the range can also be cut into innovative boomerang & triangle shapes.



Floor:  
3FEA106



Langram  
3FEA100



Roster  
3FEA106



Larden  
3FEA103







Promodo  
3FEA104







Floor:  
3FEA100

## SIZES AND FINISHES

				
	300x600 9.5mm	450x900 10mm	600x600 10mm	600x1200 11mm
All colours	● ▲	● □	● □	● □
			● Matt R10	□ Polished R9
				▲ Anti Slip R12

## SHAPES

			
Boomerang	Triangle	Honeycomb	Diamond
250x580mm	407x470mm	380x445mm	220x380mm
Available in all colours and finishes	Available in all colours and finishes	Available in all colours and finishes	Available in all colours and finishes

Please ask for details. Minimum order quantity: 20m<sup>2</sup>

## NOTES

To avoid lippage we recommend the use of self-levelling spacers

## APPEARANCE

Quartzite

## MATERIAL

Porcelain

## USAGE

Floors and Walls

## SHADE VARIATION

V4 - Heavy

## SPECIAL PIECES

Available in all colours.

For more information contact our sales team.


## SKIRTING

94x300mm

94x443mm

94x593mm

94x600mm




## STEP TREAD

300x600mm

330x593mm

330x893mm

330x1200mm




## GRADONE

300x600mm

330x593mm

330x893mm

330x1200mm



## ISO 10545 RESULTS

### 2. DIMENSIONS AND SURFACE QUALITY

Conforms

### 3. WATER ABSORPTION

$\leq 0.5\%$

### 4. FLEXURAL STRENGTH

35 N/mm<sup>2</sup>

### 6. DEEP ABRASION RESISTANCE

No rating

### 8. LINEAR THERMAL EXPANSION

$9 \times 10^{-6} \text{ } ^\circ\text{C}$

### 9. THERMAL SHOCK RESISTANCE

Conforms

### 10. MOISTURE EXPANSION

No rating

### 12. FROST RESISTANCE

Conforms

### 13. CHEMICAL RESISTANCE

Conforms

### 14. STAIN RESISTANCE

Conforms

### SLIP RESISTANCE (DIN 51130-51097)

Matt R10


Polished R9

Anti Slip R12

## MANUFACTURER CERTIFICATIONS:

EPD: Available

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to BS EN 16165:2021. HSE surface roughness and NCS Colour values are also available upon request. All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2024. 008.

 > 45%  
Pre-consumer