

Grain

4 COLOURS | 2 FINISHES | 4 SIZES



S
O
L
U
S

Floor:
3GRA102

Grain

Grain achieves a hyper-realistic oiled wood effect with hand planed surfaces that reflect light with slight chiaroscuro. Knots and veining flow over a semi-matt finished background.



Floor:
3GRA104

Grain



ABOVE
Floor:
3GRA102

RIGHT
Floor:
3GRA103



ABOVE
Floor:
3GRA101



GRA-Beige
3GRA101



GRA-Gold
3GRA102



GRA-Ash
3GRA103



GRA-Brown
3GRA104



Floor:
3GRA104

SIZES AND FINISHES

	75x450 9mm Chevron A	75x450 9mm Chevron B	200x1200 9mm	200x1800 9.5mm	300x1800 20mm
GRA-Beige	♥	♥	♥ △	♥	
GRA-Gold	♥	♥	♥ △	♥	△
GRA-Ash	♥	♥	♥ △	♥	△
GRA-Brown	♥	♥	♥ △	♥	

♥ Natural R9 △ Anti Slip R11 (A+B+C)

NOTES

To avoid lippage we recommend the use of self-levelling spacers.

Grain

APPEARANCE

Wood

MATERIAL

Porcelain

USAGE

Floors and Walls

SHADE VARIATION

V3 - Moderate


SPECIAL PIECES

Available in all colours.

For more information contact our sales team.

BATTISCOPIA

60x600x9mm



ISO 10545 RESULTS

2. DIMENSIONS AND SURFACE QUALITY

Conforms

3. WATER ABSORPTION

$\leq 0.1\%$

4. FLEXURAL STRENGTH

$\geq 40 \text{ N/mm}^2$

6. DEEP ABRASION RESISTANCE

$\leq 150 \text{ mm}^3$

8. LINEAR THERMAL EXPANSION

$\leq 7 \text{ (MK)}^{-1}$

9. THERMAL SHOCK RESISTANCE

Conforms

10. MOISTURE EXPANSION

No rating

12. FROST RESISTANCE

Conforms

13. CHEMICAL RESISTANCE

Conforms

14. STAIN RESISTANCE

Conforms

SLIP RESISTANCE (DIN 51130-51097)

Natural R9

Anti Slip R11 (A+B+C)

MANUFACTURER CERTIFICATIONS:



EPD: Available

ISO 14001

ISO 17889-1

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to BS EN 16165:2021. HSE surface roughness and NCS Colour values are also available upon request. All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2026. 004.