

# Gritstone

4 COLOURS | 3 FINISHES | 7 SIZES



S  
O  
LUS

Floor:  
2VXT104  
Wall:  
2VXT104

# Gristone

Gristone takes on the appearance of manually mixed, coarse grained concrete, complete with dynamic gritty clusters and randomly scattered pieces of gravel.



Floor:  
2VXT101



Doran  
2VXT101



Gortree  
2VXT104



Leode  
2VXT102



Cairnhill  
2VXT103



Floor:  
2VXT104

## SIZES AND FINISHES

	300x600 9mm	600x600 9mm	600x1200 9mm	750x750 9mm	750x1500 9mm	900x900 20mm	1200x1200 9mm
Doran	● \	● \	● \	● \	● \		● \
Gortree	● \	● \	● \	● \	● \		● \
Leode	● \	● \	● \	● \	● \	△	● \
Cairnhill	● \	● \	● \	● \	● \		● \

● Matt R10 (A+B)    \ Matt    △ Anti Slip R11 (A+B+C)

**APPEARANCE**  
Concrete


**MATERIAL**  
Porcelain

**USAGE**  
Floors and Walls

**SHADE VARIATION**  
V3 - Moderate

**SPECIAL PIECES**  
Available in all colours.  
For more information contact our sales team.

**BATTISCOPIA**  
70x600mm  
70x750mm



## ISO 10545 RESULTS

**2. DIMENSIONS AND SURFACE QUALITY**  
Conforms

**3. WATER ABSORPTION**  
0.2%

**4. FLEXURAL STRENGTH**  
Conforms

**6. DEEP ABRASION RESISTANCE**  
Conforms

**8. LINEAR THERMAL EXPANSION**  
7 MK<sup>-1</sup>

**9. THERMAL SHOCK RESISTANCE**  
Conforms

**10. MOISTURE EXPANSION**  
No rating

**12. FROST RESISTANCE**  
Conforms

**13. CHEMICAL RESISTANCE**  
Conforms


**14. STAIN RESISTANCE**  
Class 5

**SLIP RESISTANCE  
(DIN 51130-51097)**  
Matt R10 (A+B)  
Anti Slip R11 (A+B+C)

## MANUFACTURER CERTIFICATIONS:

**Declare.** EPD: Available  
ISO 14001  
ISO 17889-1

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to BS EN 16165:2021. HSE surface roughness and NCS Colour values are also available upon request. All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2024. 006.

 20%  
Pre-consumer