

Gritstone

4 COLOURS | 3 FINISHES | 6 SIZES



S
O
LUS

Floor:
2VXT104
Wall:
2VXT104

Gristone

Gristone takes on the appearance of manually mixed, coarse grained concrete, complete with dynamic gritty clusters and randomly scattered pieces of gravel.



Floor:
2VXT101



Doran
2VXT101



Gortree
2VXT104



Leode
2VXT102























































Cairnhill
2VXT103



Floor:
2VXT104

SIZES AND FINISHES

	 300x600 9mm	 600x600 9mm	 600x1200 9mm	 750x750 9mm	 900x900 20mm	 1200x1200 9mm
 Doran	 	 	 	 		 
 Gortree	 	 	 	 		 
 Leode	 	 	 			 
 Cairnhill	 	 	 	 		 

 Matt R10 (A+B)  Matt  Anti Slip R11 (A+B+C)

APPEARANCE
Concrete


MATERIAL
Porcelain

USAGE
Floors and Walls

SHADE VARIATION
V3 - Moderate

SPECIAL PIECES
Available in all colours.
For more information contact our sales team.

BATTISCOPA
70x600mm
70x750mm



ISO 10545 RESULTS

2. DIMENSIONS AND SURFACE QUALITY
Conforms

3. WATER ABSORPTION
0.2%

4. FLEXURAL STRENGTH
Conforms

6. DEEP ABRASION RESISTANCE
Conforms

8. LINEAR THERMAL EXPANSION
7 MK⁻¹

9. THERMAL SHOCK RESISTANCE
Conforms

10. MOISTURE EXPANSION
No rating

12. FROST RESISTANCE
Conforms

13. CHEMICAL RESISTANCE
Conforms

14. STAIN RESISTANCE
Class 5

SLIP RESISTANCE
(DIN 51130-51097)
Matt R10 (A+B)
Anti Slip R11 (A+B+C)

MANUFACTURER CERTIFICATIONS:

EPD: Available
Declare. ISO 14001
ISO 17889-1

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to BS EN 16165:2021. HSE surface roughness and NCS Colour values are also available upon request. All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2025. 007.

20%
Pre-consumer