

Inspiration

6 COLOURS | 3 FINISHES | 8 SIZES | 2 MOSAICS | 1 DECOR



S
O
LUS

Floor:
2CHT104

Inspiration

Reflecting the natural elegance of limestone, Inspiration is a highly evocative series of neutrally toned core products, which sit alongside modular and mosaic options in complementary colours.



Floor:
2CHT101

Inspiration



ABOVE
Floor:
2CHT102

RIGHT
Floor:
2CHT101



ABOVE
Floor:
2CHT106



Apostolic
2CHT101



Stimulate
2CHT102



Incentivise
2CHT103



Creatively
2CHT104



Promethean
2CHT105



Engage
2CHT106



DECORS AND MOSAICS




Modular Design *

300x600 / 600x900 / 600x1200x9mm

Available in all finishes

Available in all colours




Mosaic A

300x300x9mm (50x50mm Chips)

Natural R10

Available in all colours



Mosaic B

300x300x9mm (50x150mm Chips)















Natural R10

Available in all colours

NOTES

* Selected modular design consists of three sizes packed in a box.

SIZES AND FINISHES

	 100x300 9mm	 300x600 9mm	 450x900 9mm	 600x600 9mm	 600x600 20mm	 600x1200 9mm	 600x1200 20mm	 900x900 9mm
 Apostolic	♥	♥ \ △	♥ \	♥ \ △	△	♥ \ △	△	♥ \
 Stimulate	♥	♥ \ △	♥ \	♥ \ △		♥ \ △		♥ \
 Incentivise	♥	♥ \ △	♥ \	♥ \ △		♥ \ △		♥ \
 Creatively	♥	♥ \ △	♥ \	♥ \ △	△	♥ \ △	△	♥ \
 Promethean	♥	♥ \ △	♥ \	♥ \ △	△	♥ \ △	△	♥ \
 Engage	♥	♥ \ △	♥ \	♥ \ △	△	♥ \ △	△	♥ \

♥ Natural R10 \ Honed △ Anti Slip R11 (A+B)

Inspiration

APPEARANCE
Limestone


MATERIAL
Porcelain

USAGE
Floors and Walls


SHADE VARIATION
V3 - Moderate

SPECIAL PIECES
Available in all colours.
For more information contact our sales team.


BULLNOSE
70x600mm
70x900mm




STEP TREAD
300x600mm
300x1200mm



GRADONE
330x1200mm



ANGOLARE
330x1200mm



ISO 10545 RESULTS

2. DIMENSIONS AND SURFACE QUALITY
Conforms

3. WATER ABSORPTION
< 0.1%

4. FLEXURAL STRENGTH
> 45 N/mm²

6. DEEP ABRASION RESISTANCE
≤ 150 mm³

8. LINEAR THERMAL EXPANSION
6x10⁻⁶/°C

9. THERMAL SHOCK RESISTANCE
Conforms

10. MOISTURE EXPANSION
No rating

12. FROST RESISTANCE
Conforms

13. CHEMICAL RESISTANCE
Conforms

14. STAIN RESISTANCE
Conforms

**SLIP RESISTANCE
(DIN 51130-51097)**
Natural R10
Anti Slip R11 (A+B)

MANUFACTURER CERTIFICATIONS:



EPD: Available
ISO 14001

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to BS EN 16165:2021. HSE surface roughness and NCS Colour values are also available upon request. All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2024. 005.