

Paleon

4 COLOURS | 3 FINISHES | 10 SIZES | 2 MOSAICS | 1 DECOR



S
O
LUS



Floor:
2PEL102

A soft limestone effect with decorative textures and mosaics. Elegant tones in large formats and anti-slip finishes.



SOLUS

Solus Plus ranges are responsibly sourced in line with the BES 6001 standard.

For more information, [click here](#)

Floor:
2PEL104
Wall:
2PEL104

Paleon



ABOVE
Floor:
2PEL102
Wall:
2PEL102

RIGHT
Floor:
2PEL103



ABOVE
Wall:
2PEL104D001



PEL-Pearl
2PEL103



PEL-Champagne
2PEL101



PEL-Grey
2PEL102



PEL-Sable
2PEL104



PEL-Pearl Decor
2PEL103D001
600x1200x9mm
 Textured



PEL-Champagne Decor
2PEL101D001
600x1200x9mm
 Textured



PEL-Grey Decor
2PEL102D001
600x1200x9mm
 Textured



PEL-Sable Decor
2PEL104D001
600x1200x9mm
 Textured

















PEL-Mosaic A
2PEL105M001
260x235x9mm Chevron
 Matt R10 (A+B)



PEL-Mosaic B
2PEL106M001
260x235x9mm Chevron
 Matt R10 (A+B)

Floor:
 2PEL103
 Wall:
 2PEL103
 2PEL106M001

SIZES AND FINISHES

										
	300x600 9mm	600x600 9mm	600x600 20mm	600x1200 9mm	600x1200 20mm	750x1500 9mm	800x800 9mm	800x800 20mm	1200x1200 9mm	1200x2780 6mm
 PEL-Pearl	● △	● △		● △		●	●		● △	♥
 PEL-Champagne	● △	● △	△	● △	△	●	●	△	● △	♥
 PEL-Grey	● △	● △	△	● △	△	●	●	△	● △	♥
 PEL-Sable	● △	● △		● △		●	●		● △	

♥ Matt ● Matt R10 (A+B) △ Anti Slip R11 (A+B+C)

APPEARANCE
Limestone


MATERIAL
Porcelain

USAGE
Floors and Walls

SHADE VARIATION
V3 - Moderate

SPECIAL PIECES
For more information contact our sales team.

BATTISCOPIA
70x600mm
70x750mm



ISO 10545 RESULTS

2. DIMENSIONS AND SURFACE QUALITY
Conforms

3. WATER ABSORPTION
 $\leq 0.2\%$

4. FLEXURAL STRENGTH
 $\geq 35 \text{ N/mm}^2$

6. DEEP ABRASION RESISTANCE
 $\leq 175 \text{ mm}^3$

8. LINEAR THERMAL EXPANSION
 $7.0 \times 10^{-6} \text{ }^\circ\text{C}$

9. THERMAL SHOCK RESISTANCE
Conforms

10. MOISTURE EXPANSION
 $\leq 0.02\% \text{ (}0.2 \text{ mm/m)}$

12. FROST RESISTANCE
Conforms

13. CHEMICAL RESISTANCE
Conforms

14. STAIN RESISTANCE
Conforms

**SLIP RESISTANCE
(DIN 51130-51097)**
Matt R10 (A+B)
Anti Slip R11 (A+B+C)

CERTIFICATIONS:



EPD: Available
ISO 14001
ISO 17889-1
SASO-Approved

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to BS EN 16165:2021. HSE surface roughness and NCS Colour values are also available upon request. All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2025. 001.

The logo consists of the word "SOLUS" in a large, white, sans-serif font, stacked vertically. To the right of the middle letter "O" is a green circular icon containing a white plus sign (+).

S
O
LUS

About Solus Plus

Solus Plus is our new mark of assurance for responsibly sourced products. Built on the rigorous standards of BES 6001, it highlights collections produced by factories that demonstrate industry-leading sustainability across their entire supply chain, from raw material extraction to final delivery.

When specified through Solus, these products can contribute valuable credits toward BREEAM, LEED and WELL certification, helping you meet your environmental targets without compromising on quality or design. Look for the Solus Plus symbol to specify with confidence.

[Visit our website to learn more.](#)

[Back to top](#)