

Sherwood

5 COLOURS | 2 FINISHES | 4 SIZES



S
O
L
U
S

Floor:
3DSR103
Wall:
3DSR103

Sherwood

Truly authentic wood effect porcelain tiles, the Sherwood range provides a slightly worn, aged-timber aesthetic that lends a charming, vintage charm to any space.



Floor:
3DSR105





Whiteleaf
3DSR105



Kielder
3DSR101



Dornoch
3DSR102



Argyll
3DSR103



Arden
3DSR104



Floor:
3DSR104
Wall:
3DSR104

SIZES AND FINISHES

| | 200x1200 9mm | 250x1510 9mm | 400x1200 20mm | 600x1200 9mm |
|-------------|-----------------|-----------------|-----------------------|-----------------|
| All colours | ♥ △ | ♥ △ | △ | ♥ △ |
| | ♥ Natural R10 | | △ Anti Slip R11 (A+B) | |

NOTES

To avoid lippage we recommend the use of self-levelling spacers

APPEARANCE

Wood

MATERIAL

Porcelain

USAGE


Floors and Walls

SPECIAL PIECES

More special pieces are available.
For more information contact our sales team.

BATTISCOPA

70x1200mm




GRADINO

200x1200mm




BORDO ANGOLARE INTERNO / ESTERNO

600x600mm




GRIGLIA

130x400mm



GRIGLIA ANGOLARE

130x400mm



ISO 10545 RESULTS

2. DIMENSIONS AND SURFACE QUALITY

Conforms

3. WATER ABSORPTION

$\leq 0.1\%$

4. FLEXURAL STRENGTH

$> 45 \text{ N/mm}^2$

6. DEEP ABRASION RESISTANCE

No rating

8. LINEAR THERMAL EXPANSION

$6 \times 10^{-6} \text{ }^\circ\text{C}$

9. THERMAL SHOCK RESISTANCE

No rating

10. MOISTURE EXPANSION

No rating

12. FROST RESISTANCE

Conforms

13. CHEMICAL RESISTANCE

Conforms

14. STAIN RESISTANCE

Conforms

SLIP RESISTANCE (DIN 51130-51097)

Natural R10
Anti Slip R11 (A+B)

MANUFACTURER CERTIFICATIONS:



EPD: Available
ISO 14001

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to BS EN 16165:2021. HSE surface roughness and NCS Colour values are also available upon request. All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2024. 009.