

12 COLOURS | 3 FINISHES | 4 SIZES

Technici Gres 4

S
LUS



Floor:
2RPV449

Technici Gres 4

Practical everyday style ideally suited for commercial projects, Technici Gres 4 is a highly technical range of porcelain floor and wall tiles available in a variety of colours and sizes.



Floor:
2RPV419

Technici Gres 4



Floor:
2RPV408
2RPV450

Wall:
2RPV408
2RPV450





Felinfach
2RPV408



Dehar
2RPV535



Piling
2RPV549



Lachen
2RPV458



Merthyr
2RPV412



Jazmin
2RPV537



Nethy
2RPV419



Cohen
2RPV540



Bunker
2RPV449



Llandoverly
2RPV410



















Landsale
2RPV505



Dusken
2RPV450

SIZES AND FINISHES

	 200x200 8.3mm	 300x300 8.3mm	 300x600 9.2mm	 600x600 10.5mm
 Felinfach	● △	● ▲ △	●	●
 Dehar		●		
 Piling	● △	●		
 Lachen		●		
 Merthyr	● △	● ▲		
 Jazmin		●		
 Nethy		● △		
 Cohen	●	● ▲		
 Bunker	● △	● ▲ △	●	●
 Llandoverly		● △		
 Landsale	● △	● ▲ △		
 Dusken		● △		

● Matt R10 ▲ Textured R11 (A+B+C) △ Anti Slip R12 (A+B+C)



Anti Slip R12 (A+B+C)



Textured R11 (A+B+C)

Technici Gres 4

APPEARANCE

Speckled

MATERIAL

Porcelain

USAGE

Floors and Walls

SHADE VARIATION

V1 - Uniform


SPECIAL PIECES

For more information contact our sales team.

STEP TREAD

297x297x8.3mm


297x597x9.2mm



CUT SKIRTING BOARD ROUNDED EDGE

95x297mm

95x597mm



PRESSED COVE BASE SIT-IN

297x297x8.3mm

297x597x9.2mm



INTERNAL/EXTERNAL ANGLE

FOR COVE BASE

25x97x8.3mm



ISO 10545 RESULTS

2. DIMENSIONS AND SURFACE QUALITY

Conforms

3. WATER ABSORPTION

$\leq 0.08\%$

4. FLEXURAL STRENGTH

35 N/mm²

6. DEEP ABRASION RESISTANCE

130 mm³

8. LINEAR THERMAL EXPANSION

$7 \times 10^{-6} \text{ } ^\circ\text{C}$

9. THERMAL SHOCK RESISTANCE

Conforms

10. MOISTURE EXPANSION

No rating

12. FROST RESISTANCE

Conforms

13. CHEMICAL RESISTANCE

No rating

14. STAIN RESISTANCE

Class 2

SLIP RESISTANCE (DIN 51130-51097)

Matt R9

Textured R11 (A+B+C)

Anti Slip R12 (A+B+C)

MANUFACTURER CERTIFICATIONS:

EPD: Available

ISO 14001

For LEED, BREEAM and WELL information, please ask for details. On request tiles can be tested to BS EN 16165:2021. HSE surface roughness and NCS Colour values are also available upon request.

All sizes shown are nominal. Due to the printing process and differing screen values actual tile colours may vary. E&OE. © Solus Ceramics Limited 2024. 010a.

